




Kingfisher Company, inc.

Beam 200 Series Single-ended Reflected Type Beam Smoke Detector



Features:

- 16 to 328 foot protection range
- Single-ended, reflective design
- User friendly alignment procedure
- 6 user selectable sensitivity levels
- Optional integral NFPA 72 sensitivity test features
- Removable plug-in terminal blocks
- Digital display for easy alignment
- Paintable Cover
- Easiest alignment in the industry
- Remote test station optional



Description:

Kingfisher Model BEAM200 is an intelligent projected beam smoke detector. It is uniquely suited for protecting open areas with high ceilings where other methods of smoke detection are difficult to install and maintain. It is to be used with KCI compatible control panels only. Installation of the single-ended reflective design is much easier than dual ended projected beam detectors. Alignment is quickly accomplished via an optical sight and a 2-digit signal strength meter incorporated into the product. Listed for operation from -22°F to 131°F , BEAM200 can be used in open area applications to provide early warning in environments where temperature extremes exceed the capability of other types of smoke detection.

BEAM200S is equipped with an integral sensitivity test feature that consists of a test filter attached to a servo motor inside the detector optics. Using the remote test station RTS451, the motor is activated and moves the filter in the pathway of the light beam, thereby testing detector sensitivity. This integral sensitivity test feature allows the user to quickly and easily meet the annual maintenance and test requirements of NFPA 72.

Operation:

BEAM200 consists of a transmitter/receiver unit and a reflector. When smoke enters the area between the unit and the reflector it causes a reduction in the signal and, when the smoke level reaches the predetermined threshold, an alarm is activated.

BEAM200 has four standard sensitivity selections along with two Acclimate settings. When either of the two Acclimate settings are selected the detector will automatically adjust its sensitivity using advanced software algorithms to select the optimum sensitivity for the specific environment.

Specifications:

On smooth ceilings, 30 – 60 feet between projected beams and not more than one-half that spacing between a projected beam and a sidewall. Other spacing may be used depending on ceiling height, airflow characteristics, and response requirements. See NFPA 72.

Protection Range:	16 ft. to 328 ft. (5m to 100m)
Operating Temperature Range:	-22°F to 131°F (-30° to 55°C)
Operating Humidity Range:	10% to 93% relative humidity (non-condensing)
Adjustment Angle:	+/- 10 Degrees horizontal & vertical (The optics move independent of the unit)
Voltage:	15 to 32 VDC
Avg. Standby Current:	2mA Max
Avg. Current During Testing:	500mA Max
Alarm Current:	8.5mA Max
Fault Current:	4.5mA Max
Alignment Mode Current(24VDC):	20mA Max

Mechanical Specifications:

Detector Dimensions:	10"H x 7.5"W x 3.3"D (254mmH x 191mmW x 84mmD)
Reflector Dimensions(16' to 230'):	7.9" x 9.1" (200 x 230mm)
Reflector Dimensions (Beyond 230'):	15.7" x 18.1" (400 x 460mm)

ORDERING INFORMATION

KCi #	Model #	Description
52819	KFBEAM200	Beam Detector—Intelligent, Single-Ended, includes 8"
52820	KFBEAM200S	Beam Detector—Intelligent, Single-Ended, includes 8" Reflector & Integral Sensitivity Test
52821	KFBEAMLRK	Long Range Accessory Kit—Required for distances in excess of 70m/230ft, Includes Three (3) Additional Reflectors
52822	KFBEAMMMK	Multi-Mount Kit
52823	KFBEAMSMK	Surface Mount Kit
52828	KFBEAMHK	Heater Kit—for Beam Detector
52847	KFBEAMHKR	Heater Kit– for Beam Detector Reflector
52819-DTS		Specification Data Sheet


Kingfisher Company, inc., products must be used within their published specifications and must be PROPERLY specified, applied, installed, operated, maintained and operationally tested in accordance with their installation instructions at the time of installation and at least twice a year or more often and in accordance with local, state and federal codes, regulations and laws. Specification, application, installation, operation, maintenance and testing must be performed by qualified personnel for proper operation in accordance with all of the latest National Fire Protection Association (NFPA), Underwriters' Laboratories (UL), National Electrical Code (NEC), Occupational Safety and Health Administration (OSHA), local, state, county, province, district, federal and other applicable building and fire standards, guidelines, regulations, laws and codes including, but not limited to, all appendices and amendments and the requirements of the local authority having jurisdiction (AHJ).

NOTE: Due to continuous development of our products, specifications and offerings are subject to change without notice in accordance with Kingfisher Company, inc., standard terms and conditions


Kingfisher Company, inc. 81 Old Ferry Road - Lowell, MA 01854
Phone: 978-596-0214 Fax: 978-596-0217 www.kfci.com

DRAWINGS OR DIAGRAMS

Diagrams:



Activated Test Feature (BEAM200S ONLY)



Kingfisher Company, inc. 81 Old Ferry Road - Lowell, MA 01854
 Phone: 978-596-0214 Fax: 978-596-0217 www.kfci.com

BLANK PAGE LEFT
INTENTIONALLY

Kingfisher Company, inc. 81 Old Ferry Road - Lowell, MA 01854
Phone: 978-596-0214 Fax: 978-596-0217 www.kfci.com