



Kingfisher Company, inc.

**12-28VDC Outdoor
Strobe Low Profile**



Red KF500P Series Outdoor Strobe

Features:

- 12-28 VDC Input
- Built-In RFI Filters
- Solid State Power Supply
- 10,000 Hour Strobe Lamp
- Available in Red and Clear Lens Colors
- NEMA 4X Rated
- UL Listed

Description:

The KF500P Series strobes are polarity protected and have built-in filters to protect against radio interference and spike voltages. The model KF500P features a fully potted, Lexan®, multi-purpose mounting base which is vibration and water resistant, and a field replaceable plug-in strobe lamp. The power supply output is 8 watts and generate 6 joules per flash.

Specifications:

Flash Rate:	70 to 90 flashes per minute
Light Output:	200 candela eff. (Clear) - 80 candela eff. (Red)
Size and Weight:	5.25" tall x 5.5" dia. x 2 lbs (133mm x 140mm x 0.9kg)
Voltage and Amperage:	12-28VDC draws 0.8A average @ 12VDC tapering to 0.4A average @ 24VDC
Pipe Mount:	Use 1/2-14 NPSL Straight Pipe Thread

ORDERING INFORMATION

KCi #	Model #	Description
81116	KF500P-1228R	Red 12-24VDC Strobe Light (80 Candella Eff) 1/2" female pipe mount
81117	KF500P-1228C	Clear 12-24VDC Strobe Light (200 Candella Eff) 1/2 " female pipe mount
81116-DTS		Specification Data Sheet

Kingfisher Company, inc., products must be used within their published specifications and must be PROPERLY specified, applied, installed, operated, maintained and operationally tested in accordance with their installation instructions at the time of installation and at least twice a year or more often and in accordance with local, state and federal codes, regulations and laws. Specification, application, installation, operation, maintenance and testing must be performed by qualified personnel for proper operation in accordance with all of the latest National Fire Protection Association (NFPA), Underwriters' Laboratories (UL), National Electrical Code (NEC), Occupational Safety and Health Administration (OSHA), local, state, county, province, district, federal and other applicable building and fire standards, guidelines, regulations, laws and codes including, but not limited to, all appendices and amendments and the requirements of the local authority having jurisdiction (AHJ).

NOTE: Due to continuous development of our products, specifications and offerings are subject to change without notice in accordance with Kingfisher Company, inc., standard terms and conditions

Kingfisher Company, inc. 81 Old Ferry Road - Lowell, MA 01854
Phone: 978-596-0214 Fax: 978-596-0217 www.kfci.com