



Kingfisher Company, inc.

Kingfisher Enclosure Trim Flush Kits



*99420-08 With 91723 (FM-S)
STAR-ELT with Interior Wall mounted
Semi-Flush Trim Kit*



*99911-R-R-PN-1 With 91724 (FM-C)
Callbox with Exterior Wall mounted
Semi-Flush Trim Kit*

Features:

- Clean seamless design
- 2 Colors Option (Red or Black)
- Easy to install
- #16 GA Steel
- Built in gasket compression stop around the opening for Callbox

Description:

The Kingfisher Company, inc. Enclosure Trim Kits comes in three different styles and two color options (Red or Black) that provides a clean seamless look around any kingfisher wall mounted enclosures.

Kingfisher Enclosure Trim Kit FM-L & FM-S are easy to install and require no hand tools for installation for indoor enclosures. Kingfisher FM-L and FM-S will cover a 1.5" area around Kingfisher enclosures. Kingfisher FM-L will fit around a 30"H x 16.25"W enclosure. Kingfisher FM-S will fit around a 18"H x 12"W enclosure.

Kingfisher Enclosure Trim Kit FM-C are easy to install for Callbox. Kingfisher FM-C comes with mounting hardware for the Callbox with tamper proof screws and mudbox. Kingfisher FM-C overall dimension is 20"H x 16"W. Mudbox dimension is 18.5"H x 14"W x 4.25"D.

ORDERING INFORMATION

KCi #	Model #	Description
91722	FM-L	Semi-flush Mount Kit, Large Enclosure, Red (For use with 99420-20, 99420-28, 99420-36, 99420-44, 99433-IOT-16, 99433-IOT-24, 99433-IOT-32, & 99433-IOT-40)
91722-B	FM-L-B	Semi-flush Mount Kit, Large Enclosure, Black (For use with 99420-20, 99420-28, 99420-36, 99420-44, 99433-IOT-16, 99433-IOT-24, 99433-IOT-32, & 99433-IOT-40)
91723	FM-S	Semi-flush Mount Kit, Small Enclosure, Red (For use with 99420, 99421, 99420-IOT, 99420-12 & 99433-IOT-08)
91723-B	FM-S-B	Semi-flush Mount Kit, Small Enclosure, Black (For use with 99420, 99421, 99420-IOT, 99420-12 & 99433-IOT-08)
91724	FM-C	Callbox Exterior Semi-flush Mount Kit, Red (For use with 99911)
91724-B	FM-C-B	Callbox Exterior Semi-flush Mount Kit, Black (For use with 99911)

Kingfisher Company, inc., products must be used within their published specifications and must be PROPERLY specified, applied, installed, operated, maintained and operationally tested in accordance with their installation instructions at the time of installation and at least twice a year or more often and in accordance with local, state and federal codes, regulations and laws. Specification, application, installation, operation, maintenance and testing must be performed by qualified personnel for proper operation in accordance with all of the latest National Fire Protection Association (NFPA), Underwriters' Laboratories (UL), National Electrical Code (NEC), Occupational Safety and Health Administration (OSHA), local, state, county, province, district, federal and other applicable building and fire standards, guidelines, regulations, laws and codes including, but not limited to, all appendices and amendments and the requirements of the local authority having jurisdiction (AHJ).

NOTE: Due to continuous development of our products, specifications and offerings are subject to change without notice in accordance with Kingfisher Company, inc., standard terms and conditions

Kingfisher Company, inc. 81 Old Ferry Road - Lowell, MA 01854
 Phone: 978-596-0214 Fax: 978-596-0217 www.kfci.com